




PORTABLE COMPACTOR RANGE

The  range of Heavy duty - Portable Compactors are particularly versatile and can compact general mixed waste at a ratio of up to **5:1**.

Each unit is built to withstand the rigours of daily use and is fitted with twin hydraulic ram systems, with compaction forces available within the range from 25-34 Tonnes (40 tonne available at extra cost). Additionally, each unit carries a full 2 Year on site warranty, thus you are assured of the durability and reliability. These types of unit are particularly useful, if you have site constraints, being: -

- Reduced Headroom
- Security Issues
- Fire risks – i.e. open site
- Space Restrictions – i.e. Length
- Vermin Problems
- Odorous Waste Products

All Machines are built to exacting Standards, with full seam welding and Nylon wear pads for longevity of use.

Units are manufactured to C.H.E.M Standards (Container Handling Equipment Manufacturers) and comply with all UK waste handling requirements.



Specification	AJK6-14E – Skip Type	AJK14-26N – Roll on Off
Capacities	6-14 cubic Metres	14-26 cubic Metres
Motor Rating	4KW	5.5KW
Press Force	25 Tonne (Twin ram)	34 Tonne (Twin ram)
Loading Aperture	1600mm x 1250mm	1650mm x 2050mm
Cycle Time	39 Seconds	23 Seconds
Volume Per Stroke (CHEM)	1.15m ³	1.14m ³
Volume Per Hour	106m ³	178m ³
Ram penetration	300mm	300mm
Power Supply Required	3 Phase 415V – 16 amp	3 Phase 415V – 25amp